
Folsom Powerplant Central Valley Project



Plant Contact:

Thomas J. Aiken, Area Manager Central California Area Office

Plant Address:

Folsom Powerplant Central California Area Office 7794 Folsom Dam Road Folsom CA 95630

Telephone Numbers:

Phone: (916) 988-1707 Fax: (916) 989-7208

E-Mail Address:

taiken@mp.usbr.gov

Reclamation Region: Mid-Pacific

NERC Region: Western Electricity Coordinating Council, California-Southern Nevada

Power Area

PMA Service Area: Western Area Power Administration, Sierra Nevada Region

Project Authorization: Funds for construction of the initial features of the Central Valley

Project were provided by the Emergency Relief Appropriation Act of 1935 (49 Stat. 115). The Secretary of the Interior authorized the project and the President approved it on December 2, 1935.

Project Purposes: The Central Valley Project, one of the Nation's major water

conservation developments, extends from the Cascade Range on the north to the semiarid but fertile plains along the Kern River on the south. Initial features of the project were built primarily to protect the Central Valley from crippling water shortages and menacing floods. New project units were built to provide water and power to match the

continued growth of the State.

Although developed primarily for irrigation, this multiple-purpose project also provides flood control, improves Sacramento River navigation, supplies domestic and industrial water, generates electric power, conserves fish and wildlife, creates opportunities for recreation,

and enhances water quality.

Plant Location: Folsom Power plant is located on the American River in Sacramento

County, California, about 20 miles northeast of Sacramento, California

Plant Purpose: Folsom is a peaking powerplant which is dedicated first to meeting the

requirements of the project facilities. The remaining energy is marketed to various preference customers in northern California. This plant also provides power for the pumping plant, which supplies the

local domestic water supply.

Plant Facts: Folsom Dam is a concrete gravity structure 340 feet high and 36 feet

wide at the crest. The crest is 1,400 feet long. Folsom Powerplant, constructed by Reclamation, is located at the foot of Folsom Dam on the north side of the river. Water from the dam is released through

three 15-foot-diameter penstocks to three generating units.

Plant History: Folsom Dam was constructed by the Corps of Engineers and upon

completion was transferred to the Bureau of Reclamation for

coordinated operation as an integral part of the Central Valley Project. Construction of the dam began in October 1948 and was completed in

May 1955. The units were up rated in 1972.

Present Activities: Folsom Powerplant is an integral component of the Reservoir Flood

Control Operation. The power plant is used to augment early flood

control releases.

Future Planned Activities: The powerplant will continue to be used to augment early flood control

releases from the reservoir. Continued peaking operation is planned as releases permit. Folsom is providing a larger degree of local voltage

control.

Special Issues: Folsom is being increasingly relied upon to support local loads during

system disturbances.

River: American River **Plant Type:** Conventional

Powerhouse Type: Above Ground **Turbine Type:** Francis

Original Nameplate Capacity: 162,000 kW Installed Capacity: 198,720 kW

Year of Initial Operation: 1955 Age: 48 years

Net Generation (FY-2003): 550.3 GWh Rated Head: 300 feet

Average Plant Factor (FY-2003): 31.7 percent Remotely Operated: Yes

Production Mode: Intermediate

Click here for information on Folsom Dam.

Click here for information on the **Central Valley Project**.

Ancillary Services


Folsom Ancillary Services				
Spinning Reserve	Yes			
Non-Spinning Reserve	Yes			
Replacement Reserve	Yes			
Regulation/Load Following	Yes			
Black Start	Yes			
Voltage Support	Yes			


Generators


Folsom Generators Existing Number and Capacity				
Unit#	Original Capacity (kW)			
1	54,000	12,240	66,240	
2	54,000	12,240	66,240	
3	54,000	12,240	66,240	
3 Units	162,000	36,720	198,720	

The maximum operational capacity is 210,000 kW

Generation









Prime Laboratory Benchmarks


Benchmark 1 Wholesale Firm Rate





Benchmark 2
Reclamation's Production Cost as Percentage of Wholesale Firm Rate




Benchmark 3 Production Cost













Benchmark 3
Production Cost













Benchmark 4 Workforce Deployment

			Folsom			
		2003	Equival			
		W	ork Year Leve	s		
	Equiv Work Year Charged to Powerplant	Leave Additive	Denver and Washington Equiv Work Year Additive	Total Equiv Work Year Allocated to Powerplant	Total Equiv Work year per Generating Unit	Total Equiv Work Year per Megawatt
General	0	0	0.07	0.07	0.02	0
Operation	2.01	0.23	0	2.25	0.75	0.011
Maintenance	11.47	1.33	0	12.8	4.27	0.064
Total Staffing	13.48	1.57	0.07	15.12	5.04	0.08












Benchmark 5 Availability Factor




Benchmark 6 Forced Outage Factor



Benchmark 7 Scheduled Outage Factor



Starts



Benchmark Data Comparison

Fiscal Year 2003	Folsom Powerplant	Reclamation Average 100-500 MW Group	Total Reclamation Average	Industry Average	Best Performers
Wholesale Firm Rate Mills/kWh	24.6	Not Applicable	*23.1	Not Available	Not Available
Production Cost as Percentage of Wholesale Firm Rate	4.1%	Not Applicable	12.0%	Not Applicable	Not Applicable
O&M Cost \$/MWh	12.8	4.5	2.7	10.9	1.1
O&M Costs \$/MW	35,338	10,924	7,315	17,261	3,108
O&M Equiv Work Year per MW	0.1	0.1	0.04	Not Available	0.01
Availability Factor	71.8	87.6	83.6	**88.9	99.1
Forced Outage Factor	0.1	0.8	1.5	**2.4	0.0
Scheduled Outage Factor	28.1	11.7	14.9	**8.7	0.0

*Weighted by Net Generation **2002 NERC Average